



FRESH START[®] HIGH-HIDING ALL PURPOSE PRIMER K046

Features

- Maximum hiding
- Excellent all-around stain blocker
- Superior adhesion
- Whole house primer
- Quick drying
- Great flow & levelling
- Mildew resistant
- Low odour

Recommended For

Interior: Use on new or previously painted wood, plywood, drywall, ceiling tile, Formica[®], Masonite[®], ceramic tile and cured plaster. **Exterior:** Use on new or previously painted wood, fibre cement board, hardboard siding, aluminum, galvanized, cured masonry and previously coated ferrous metal surfaces.

Type of Stains: Water stains, tannin bleed, smoke damage, markers, crayons, pens, pencils, nicotine, hand & fingerprints, household stains such as coffee and many more.

2 coats of primer may be required in severe cases; allow the primer to dry thoroughly for best results.

General Description

A superior quality, interior/exterior 100% acrylic primer that delivers maximum hide and ensures uniform finish. It is the product of choice when a significant colour change is required. It provides superior adhesion and is more forgiving over difficult substrates. Additionally, this product is effective in sealing and suppressing most bleeding type stains. In cases of severe bleeding, a solvent based primer should be used to prevent stains from reappearing.

Limitations

- Not recommended for sealing knots or over pine sap.
- On hard, non-porous surfaces, such as glazed ceramics and prefinished metal, maximum adhesion and hardness may take 3-4 days to develop.
- Do not apply when air and surface temperatures are below 4.4 °C (40 °F).

Product Information

Colours: —Standard:

White (00)

White may be tinted to light pastels with up to 2.0 fl. oz. of Benjamin Moore[®] Gennex[®] colorants per 3.79 L.

For best hiding results, tint to the approximate shade of the finish coat.

—Gennex[®] Tint Bases:

Deep Base (04)

(When tinted in accordance with Benjamin Moore prescriptions, the Deep Base will provide a hiding base coat suitable for use under deep and intense colours.)

—Special Colours:

Contact your Benjamin Moore representative.

Certification:

VOC compliant in all regulated areas

Master Painters Institute MPI # 6, 17, 39, 50

Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84

LEED [®] Primer for Schools	CHPS (Collaborative for High Performance Schools)	VOC
YES	YES	44 g/l or less

Qualifies for
LEED[®]
Credit
(PRIMER)

CUSTOMER INFORMATION CENTRE:

1-800-361-5898, info@benjaminmoore.ca, www.benjaminmoore.ca

Technical Data ◊

White

Vehicle Type	100% Acrylic Latex
Pigment Type	Titanium Dioxide
Volume Solids	43%
Coverage per 3.79 L at Recommended Film Thickness	37.2 – 41.8 sq. m. (400 – 450 sq. ft.)
Recommended Film Thickness	– Wet 3.8 mils – Dry 1.4 mils
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.	
Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 1 hour – To Recoat 2 hours
High humidity and cool temperatures will result in longer dry, recoat and service times.	
Dries By	Evaporation, Coalescence
Viscosity	95 ± 2 KU
Flash Point	None
Gloss / Sheen	Low Lustre (7 – 12 @ 85°)
Surface Temperature at Application	– Min. 4.4 °C (40 °F) – Max. 32 °C (90 °F)
Thin With	Do Not Thin
Clean Up Thinner	Clean Water
Weight Per 3.79 L	4.9 kg (10.8 lbs)
Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 32 °C (90 °F)

Volatile Organic Compounds (VOC)

White - 44 g/L
Deep Base - 35 g/L

◊Reported values are for White. Contact Benjamin Moore for values of other bases or colours.

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure before applying base coat. Cured plaster should be hard, have a slight sheen and maximum PH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry. **Caution:** Smooth planed clapboards or siding must be sanded thoroughly to break the "mill glaze" allowing proper penetration and adhesion.

Difficult Substrates: If the surfaces to be painted exhibit severe tannin or smoke staining, an alkyd based Benjamin Moore primer may be your best choice for conquering these severe conditions. Consult your Benjamin Moore retailer for further guidance.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php

Primer/Finish Systems

Fresh Start® High-Hiding All Purpose Primer is the preferred primer in most situations. New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results use Fresh Start® High-Hiding All Purpose Primer tinted to the approximate finish coat colour. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

Wood and engineered wood products

Primer: Fresh Start® High-Hiding All Purpose Primer (K046)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Bleeding type woods, (cedar and redwood):

Primer: Fresh Start® High-Hiding All Purpose Primer (K046) or

Fresh Start® Multi-Purpose Oil Based Primer (F024)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Drywall

Primer: Fresh Start® High-Hiding All Purpose Primer (K046)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Plaster

Primer: Fresh Start® High-Hiding All Purpose Primer (K046)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Rough or Pitted Masonry

Primer: Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Smooth Poured or Pre-cast Concrete

Primer: Ultra Spec® Masonry Interior / Exterior 100% Acrylic Masonry Sealer (K608) or Fresh Start® High-Hiding All Purpose Primer (K046)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Ferrous Metal (Steel and Iron)

Primer: Ultra Spec HP® Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat

Non-Ferrous Metal (Galvanized & Aluminum) All new metal surfaces must be thoroughly cleaned with Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

Primer: Ultra Spec HP® Acrylic Metal Primer (FP04)

Finish: 1 or 2 coats of the appropriate Benjamin Moore® finish coat.

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir thoroughly before and during use. Apply one or two coats.

Paint Application: For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area.

This product can also be sprayed.

Spray, Airless: Fluid Pressure: 1,500 – 2,500 PSI;

Tip: .013 - .017

Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

Clean Up: Clean equipment with soap and water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or provincial environmental agency on disposal options

Environmental, Health & Safety Information.

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN

PROTECT FROM FREEZING

Refer to Safety Data Sheet for additional health and safety information.