



MAXUM[®]

SEMI-TRANSPARENT DECK & SIDING STAIN 7500 SERIES

Features

- Semi-Transparent Deck & Siding Stain
- "Wet Wood Friendly"
- Alkyd
- Gives Mildew Resistant Coating
- Blocks UV

Recommended For

For Exterior Applications: Wood Decks, Outdoor Wood Furniture, Wood Fencing, Wood Railings & Porch Trim, New Wood, Pressure Treated Wood, Weathered Wood, Fences, Wood Siding & Decorative Timbers.

General Description

Maxum[®] 7500 Semi-Transparent Deck & Siding Stain is a semi-transparent wood stain designed for use on all types of exterior wood substrates where a true semitransparent finish is desired. Its special formulation utilizes deep penetrating pigments that tone the wood adding subtle highlights to the appearance of the wood without concealing the beauty of the natural wood grain and texture. It is "Wet Wood Friendly" which allows for fast project completion. It provides excellent protection against the damaging effects of Ultra-Violet rays from the sun. It retards wood dry rot and reduces warping. It resists chalking, peeling, blistering and cracking, and is fortified to withstand foot traffic. Mildew Resistant – This paint contains agents, which inhibit the growth of mildew on the surface of this paint film.

Limitations

- Apply when surface and air ambient temperatures are above 50°F and below 90°F.
- Avoid paint application outside when weather conditions are threatening, and late in the afternoon when there is a chance of moisture condensing on wet paint.

Product Information

Colors — Standard:		Technical Data◇		Clear Base
B7500-316, New Cedar B7500-300, Natural B7500-700, Heartwood B7500-304, Redwood		C7500-300, Natural C7500-304, Redwood C7500-316, New Cedar C7500-700, Heartwood		Vehicle Type Linseed Oil - Alkyd / Alkyd
— Tint Bases:				Pigment Type N/A
B7500-27, Clear Base C7500-27, Clear Base				Volume Solids B7500 = 30.6 ± 1.0% C7500 = 57%
— Special Colors:				Coverage per Gallon at B7500 = 150-400 Sq. Ft. Recommended Film Thickness C7500 = 200-350 Sq. Ft.
Contact your dealer.				Recommended Film Thickness – Wet Penetrating-minimal – Dry Penetrating-minimal
Certification:				Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.
The C7500 [High Volume Solids] version of this product is compliant under the Ozone Transport Commission regulations as a Stain.				Dry Time @ 77°F (25°C) @ 50% RH – Tack Free B7500 4-6 Hours – To Recoat No more than 15 minutes – Full Cure 7 Days – Ready for traffic 48 Hours
This product is currently approved for use under MPI #156.				High humidity and cool temperatures will result in longer dry, recoat and service times.
Technical Assistance:				Dries By Oxidation
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554, or visit www.coronadopaint.com .				Viscosity B7500 = 12 - 15 Seconds (#4 Ford Cup) C7500 = < 50 KU (Krebs Units)
				Flash Point 105°F or greater (TT-P-141, Method 4293)
				Specular Gloss B7500 = 15 - 20 units @ 85° C7500 = Flat
				Surface Temperature at Application – Min. 50°F – Max. 90°F
				Thin With Do Not Thin
				Clean Up Thinner Mineral Spirits
				Weight Per Gallon B7500 = 7.1 lbs. C7500 = 9.24 lbs.
				Storage Temperature – Min. 45°F – Max. 95°F
				Volatile Organic Compounds (VOC)
				B7500 =541 Grams/Liter 4.51 Lbs./Gallon C7500 =229 Grams/Liter 1.91 Lbs./Gallon

◇ Reported values are for Clear Base. Contact dealer for values of other bases or colors.

Maxum® Semi-Transparent Deck & Siding Stain 7500 Series

Surface Preparation

The entire surface areas to be painted should be clean, dry, sound and free of all dirt, grease, oils, waxes, loose wood fibers, mill glaze, mildew and any other surface contaminants that may cause paint failure. Grease residue should be removed with an Oil and Grease Emulsifier. Sand off any markings used to grade or identify the wood. Any existing mill glaze should be properly sanded sufficiently to open the wood grain. Wood can be slightly damp but not wet to the touch.

Mildew – Mildew is a natural occurrence over which we have no control. Surface areas that are affected by the growth of mildew should be vigorously hand scrubbed with a soft-medium bristle brush and 1 cup of Tri-Sodium Phosphate – (TSP), or non-ammoniated detergent cleaner mixed with a solution of 1 part household bleach and 3 parts of warm water, per gallon solution. Follow manufacturer's instructions for safe handling and use of cleaning solution. Allow the solution to stand on the affected surface areas for approximately 10 – 20 minutes, then rinse with clean water and allow to dry thoroughly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Stain System

Previously Painted Wood, Latex or Oil Solid Stains or Water Sealers – All existing paint coatings must be completely removed and treated as a new wood surface. If surface was stained previously with Maxum® Semi-Transparent Deck & Siding Stain, removal of existing material is not necessary, unless water continues to bead on the surface. Removal can be completed with chemical "no wax" strippers, or by hand scraping, sanding, wire brushing and/or power tool cleaning methods. Pre-existing stains or sealers should be removed with a wood stain stripper. Any chemical residue, dead wood fibers or sawdust should be completely removed. Repair/replace any seriously damaged and/or delaminated surface areas. Thoroughly wash, rinse and allow the wood to dry totally before applying this material.

Color Testing: It is recommended to test a small area of scrap wood for color approval before you begin. Maxum® Waterborne Alkyd Stains appear slightly milky in appearance in the can and when applied to the wood surface. This is normal. Once applied, the alkyd resins begin to penetrate and bond. As this occurs, and water evaporates, the slightly milky appearance disappears.

Application

DO NOT THIN! Maxum® Semi-Transparent Deck & Siding Stain applies easily with a quality synthetic brush, roller, stain pad, or airless spray methods. Stir product thoroughly before and during application to ensure uniformity in color. Apply by brush, roller or stain pad to effectively work stain into the wood pores. Apply stain to two or three boards at a time and apply a smooth and generous coat with the wood grain, continuing the entire length of the boards or until you reach a natural break in the surface. Avoid any excessive re-spreading or reworking. Always maintain a wet edge during application by brushing/rolling into previously applied coating area. When applying by airless spray, use a unit with a minimum of 2000 psi of pressure with a 0.011 - 0.015 fluid spray tip. During spray application, back-roll/brush the surface area to ensure even application and to work stain into the wood pores. If applying a two-coat finish system, allow the first coat 5 to 10 minutes to dry then apply second finish coat in no more than 15 minutes after application of first coat, removing excess stain. Fully cures in 7 days depending upon conditions. Avoid application in direct sunlight or on windy days. Apply when surface and air ambient temperatures are above 50°F and below 90°F. Avoid paint application outside when weather conditions are threatening, and late in the afternoon when there is a chance of moisture condensing on wet paint.

THIS IS A WET ON WET APPLICATION PRODUCT. A SECOND COAT MUST BE APPLIED WITHIN 15 MINUTES!

Clean Up

Clean brushes and equipment with mineral spirits. Clean all painting tools, such as brushes, roller covers and spray equipment with the same or follow state/local guidelines on solvent use.

DANGER – Rags, steel wool or waste soaked with the product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

USE COMPLETELY OR DISPOSE OF PROPERLY.

This product contains organic solvents which may cause adverse effects to the environment if handled improperly. Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

Disposal of wastes containing either organic solvents or free-liquids in landfills is prohibited. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for local disposal options.**

Environmental Health & Safety Information

DANGER!

COMBUSTIBLE LIQUID AND VAPOR

VAPOR HARMFUL

See cautions on back panel

Contains: Petroleum Distillates

HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD. CAUSES IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT. MAY CAUSE ALLERGIC SKIN REACTION.

NOTICE: Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Keep away from heat and flame. **Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. To avoid breathing vapors or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above the applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Aspiration Hazard. Small amounts aspirated into the respiratory system may cause mild to severe pulmonary injury. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If swallowed, do not induce vomiting. Get medical attention immediately.

IN CASE OF FIRE – Use foam, CO₂, dry chemical or water fog.

SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**