

Paint Shop Atlantic Limited

1-709-747-5432

102, Clyde
Avenue

Mount Pearl, NL A1N 4S2

Technical service 1-888-758-5497
info.boomerang@laurentide.co

SECOND WIND

5387-91

Recycled Paint walls, floors and patios – Interior / Exterior

Type:	Acrylic	Size :	3.78 litres and 18.9 litres
Gloss level :	Pearl	Drying time :	Touch : 30 to 60 min. Recoat : 8-12 hours
Viscosity:	95-100 U.K.	Concentration of solids :	Per weight : 40 to 60%
Coverage :	40 m ² / 3.78 litres	COV :	43 g/L (average)
Cleaner/Thinner :	Water		

Colour : 5387-91 Urban Slate

Description: A premium quality pearl gloss recycled paint. Can be used indoors and outdoors, on walls, floors and patios. A resin is added to make the product more resistant.

Colour: This product should not be tinted (to preserve its properties).

Colour may vary slightly from batch to batch.

Restrictions:

Do not apply in direct sunlight.

Never apply under 10°C or over 32°C.

The humidity level must be lower than 50%. The area must be well ventilated

Storage: Keep in a dry and well ventilated area in moderate temperatures (20°C). Keep from freezing.

Surface preparation:

Surface preparation is the most important part of the process.

All surfaces must be clean, dry and free of contaminants. Remove all peeling paint. Glossy surfaces must be sanded to improve adhesion. Clean surfaces with TSP (Trisodium phosphate) solution and rinse well with water. Allow enough drying time.

Consult with your municipality in order to dispose of used paint properly.

- **Bare wood (non-resinous):** Apply a primer or a first coat thinned at 15% in volume with water
- **¹Bare wood (resinous):** According to wood type (pine, spruce, cedar...) apply anti-bleeding primer.
- **¹Alkyd painted surface:** Sand glossy surfaces and remove dust. Apply a transition primer.
- **Latex painted surface:** Apply as is.
- **Plaster/ New gypsum board:** Apply a latex primer
- **¹Concrete, cement:** Concrete must be dry before being painted, new concrete must dry at least one month per inch of thickness. Wash with muriatic acid and rinse thoroughly. Allow to dry. Apply first coat diluted with 10-15% of water.
- **Painted or primed metal:** Apply directly

Warning :
Keep from freezing.
Keep out of the reach children.

Prior to use this product, read the material safety data sheet for the use of proper protective equipment, for preventive measures and first-aid/emergency procedures

The information given above is provided by Laurentide re-sources for information purposes only and in no way does it constitute a representation, promise or guarantee in regards to the usage, durability or quality of the product. The products identified above must be used in strict compliance with the specifications mentioned above and all other instructions, warning or guidelines issued by Laurentide re-sources. This publication supersedes any previous one.



Paint Shop Atlantic Limited

1-709-747-5432

102, Clyde Avenue

Mount Pearl, NL A1N 4S2

Technical service 1-888-758-5497
info.boomerang@laurentide.co

SECOND WIND 5387-91

Recycled Paint walls, floors and patios – Interior / Exterior

- **Bare metal:** Consult your paint expert for more details. Drying time may vary depending on temperature, humidity, ventilation and thickness applied.

Application:

Shake well and use a stir stick to mix the content all the way to the bottom of the can.

Use a synthetic paintbrush (nylon or polyester) or a 13 mm anti-lint roller.

For spray application, dilute with water to 10 to 15% in volume to get an even spread.

For better performances, two (2) coats should be applied.

Allow enough drying time before recoating.

Cleaning of tools:

Clean with water and soft soap. Rinse well.

Instruction for maintenance:

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners and/or fatty soap. Rinse soap scum. To obtain best quality, wait at least 3 – 4 weeks prior to a first wash.

For more information, contact customer service.

You may also visit our website: www.boomerangpaint.com
or write to us cs.resources@laurentide.co

¹ For complementary information and recommendation for those substrates, if necessary, do not hesitate to consult our customer service department specialist.

Consult with your municipality in order to dispose of used paint properly.

Warning :
Keep from freezing.
Keep out of the reach children.

Prior to use this product, read the material safety data sheet for the use of proper protective equipment, for preventive measures and first-aid/emergency procedures

The information given above is provided by Laurentide re-sources for information purposes only and in no way does it constitute a representation, promise or guarantee in regards to the usage, durability or quality of the product. The products identified above must be used in strict compliance with the specifications mentioned above and all other instructions, warning or guidelines issued by Laurentide re-sources. This publication supersedes any previous one.