

Paint Shop Atlantic Limited

1-709-747-5432

102, Clyde Avenue

Mount Pearl, NL A1N 4S2

Technical service 1-888-758-5497
info.boomerang@laurentide.co

SECOND WIND

5187-XX

Recycled Latex Paint – Interior/Exterior

Type:	Acrylic	Size :	3.78 litres
Gloss level :	Velvet	Drying time :	Touch : 30 to 60 min.
Viscosity:	95-100 U.K.		Recoat : 6 – 9 hours
Coverage :	40 m ² / 3.78 litre	Concentration of solids :	Per weight : 40 to 60%
Cleaner :	Water	COV :	43 g/L (average)

Colours :	5187-10 Seasalt	5187-15 Tea Bun	5187-20 Maple Sugar
	5187-22 Driftwood	5187-23 Coastline	5187-26 Main Street
	5187-27 Light Rain	5187-28 Pineapple Crush	5187-42 Burnt Berry
	5187-70 Harbour Mist	5187-71 Landwash	

Description: Recycled latex premium low sheen paint can be used indoor and outdoor.

Colour: This product should not be tinted (to preserve its properties).

Colour may vary slightly from batch to batch.

Restrictions:

Do not apply in direct sunlight.

Never apply under 10°C or over 32°C.

The humidity level must be lower than 50%. The area must be well ventilated

Not to be used for roof, patio or floor. For vertical surfaces only.

Storage: Keep in a dry and well ventilated area in moderate temperatures (20°C). Keep from freezing.

Surface preparation:

Surface preparation is the most important part of the process.

Consult with your municipality in order to dispose of used paint properly.

All surfaces must be clean, dry and free of contaminants. Remove all peeling paint. Glossy surfaces must be sanded to improve adhesion. Clean surfaces with TSP (Trisodium phosphate) solution and rinse well with water. Allow it enough drying time.

- **Bare wood (non-resinous):** Apply a primer or a first coat thinned at 15% in volume with water
- **¹Bare wood (resinous):** According to wood type (pine, spruce, cedar...) apply anti-bleeding primer.
- **¹Alkyd painted surface:** Sand glossy surfaces and remove dust. Apply a transition primer.
- **Latex painted surface:** Apply as is.
- **Plaster/ New gypsum board:** Apply a latex primer

Warning :
Keep from freezing.
Keep out of the reach of children.

Prior to use this product, read the material safety data sheet for the use of proper protective equipment, for preventive measures and first-aid/emergency procedures

The information given above is provided by Laurentide re-sources for information purposes only and in no way does it constitute a representation, promise or guarantee in regards to the usage, durability or quality of the product. The products identified above must be used in strict compliance with the specifications mentioned above and all other instructions, warning or guidelines issued by Laurentide re-sources. This publication supersedes any previous one.



Paint Shop Atlantic Limited

1-709-747-5432

102, Clyde Avenue

Mount Pearl, NL A1N 4S2

Technical service 1-888-758-5497
info.boomerang@laurentide.co

SECOND WIND

5187-XX

Recycled Latex Paint – Interior/Exterior

• ¹**Concrete, cement:** Concrete must be dry before being painted, new concrete must dry at least one month per inch of thickness. Wash with muriatic acid and rinse thoroughly. Let dry. Apply first coat diluted with 10-15% of water.

• **Painted or primed metal:** Apply directly

• **Bare metal:** Consult your paint expert for more details.

Application:

Shake well and use a stir stick to mix the content all the way to the bottom of the can.
Use a synthetic paintbrush (nylon or polyester) or a 13 mm anti-lint roller.

To apply as a spray, dilute with water to 10 to 15% in volume to get an even spread.

For better performances, two (2) coats should be applied.

Allow enough drying time before recoating.

Drying time may vary depending on temperature, humidity, ventilation and thickness applied.

Cleaning of tools:

Clean with water and soft soap. Rinse well.

Instruction for maintenance:

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners and/or fatty soap. Rinse soap scum. For best quality performance, wait at least 3 – 4 weeks prior to a first wash.

For more information, contact customer service.

You may also visit our website: www.boomerangpaint.com
or write to us cs.resources@laurentide.co

¹ For complementary information and recommendation for those substrates, if necessary, do not hesitate to consult our customer services department specialist.

Consult with your municipality in order to dispose of used paint properly.

Warning :
Keep from freezing.
Keep out of the reach of children.

Prior to use this product, read the material safety data sheet for the use of proper protective equipment, for preventive measures and first-aid/emergency procedures

The information given above is provided by Laurentide re-sources for information purposes only and in no way does it constitute a representation, promise or guarantee in regards to the usage, durability or quality of the product. The products identified above must be used in strict compliance with the specifications mentioned above and all other instructions, warning or guidelines issued by Laurentide re-sources. This publication supersedes any previous one.