



REMOVE FINISH REMOVER K315

Features

- Removes both latex and oil finishes
- Fast-acting formula
- Removes clear finishes through solid colour stains
- Concentrated formula

General Description

This product is designed for the removal of peeling oil or latex stain, varnish, and clear-coat wood finishes. It will also remove damaged and discoloured wood fiber from all exterior wood surfaces: decking, siding, shakes and furniture. Restores wood to its natural tone and prepares the surface for recoating.

Recommended For

Residential or commercial applications. Previously finished, exterior wood surfaces.

Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F).
- Remove, Finish Remover may darken certain wood types during application. If desired, use Brighten, Brightener & Neutralizer (K317) to restore wood colour back to its natural appearance

Product Information

Colours — Standard:

Not applicable.

— Tint Bases:

Not applicable.

— Special Colours:

Not applicable

Certification:

VOC compliant in all regulated areas.

Very low in VOC's.

CUSTOMER SERVICE INFORMATION CENTRE

1-800-361-5898, info@benjaminmoore.ca, www.benjaminmoore.ca

Technical Data[∆]

N/A

Max. Mixing Ratio (4:1): 15.14 Litres of water to 3.79 Litres of REMOVE

Coverage per 3.79 Litres	Undiluted (Max. 15.16 Litres of water)	Diluted	9.29 - 18.56 sq. m. (100 - 200 sq. ft.)
Depending on dilution and surface conditions			

Surface Temperature at application	– Min.	10 °C (50 °F)
	– Max	32.2 °C (90 °F)

Flash Point None

Thin With Clean Water

Clean Up Thinner Clean Water

Weight Per 3.79 L 4.1kg (9.1 lbs)

Storage Temperature	– Min	4.4 °C (40 °F)
	– Max.	32.2 °C (90 °F)

Volatile Organic Compounds (VOC)[∆]

Exempt

Remove, Finish Remover K315

Surface Preparation

Project surfaces may be damp or dry. Do not apply if surface temperature is below 10 °C (50 °F). Protect adjacent surfaces; cover with plastic and/or tape off any areas not being stripped. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

It is recommended that you test product performance in an inconspicuous area prior to use.

PRIOR TO APPLICATION: Determine proper dilution following the chart below. Test a small, inconspicuous area and allow to dry before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture_e.html.

Application

MIXING: REMOVE, Finish Remover is a concentrate. A 3.785 litre container makes up to 18.927 Litres of product.

Multiple Coats / Solid Colour or Semi Solid Stain	Do not dilute
Weathered / Solid Colour or Semi Solid Stain	Mix 4.0 Litres of REMOVE with 4.0 Litres of water
Semi Transparent Stain	Mix 4.0 Litres of REMOVE with 7.5 Litres of water
Transparent Stain	Mix 4.0 Litres of REMOVE with 11.0 Litres of water
Clear Finish	Mix 4.0 Litres of REMOVE with 15.0 Litres of water

DO NOT MIX CLEANER IN METAL CONTAINERS. NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

1. Apply product liberally to surface with plastic garden sprayer, brush or roller.
2. Allow solution to stand for 10-30 minutes, depending on age and type of finish to be removed.
3. Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
4. Neutralize surface with BRIGHTEN, Brightener & Neutralizer (K317) following label directions.
5. Allow to dry thoroughly. **Note:** When applying to vertical surfaces, apply from bottom to top.

Mixing

Mix according to the instructions above.

CLEAN UP: Clean equipment with warm, soapy water.

DISPOSAL: USE COMPLETELY OR DISPOSE OF PROPERLY. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options

Environmental, Health & Safety Information

CAUSES BURNS

Do not swallow.
Do not get in eyes.
Do not get on skin or clothing.
Do not breathe fumes.
Handle with care.
Keep out of reach of children.
Wear rubber gloves and safety glasses.
Use only in a well-ventilated area.
Wear a mask or respirator.

FIRST AID TREATMENT

Contains sodium hydroxide and 2-butoxyethanol.
If swallowed, call a Poison Control Centre or doctor immediately.
Do not induce vomiting.
If in eyes, rinse with water for 15 minutes.
If on skin, rinse well with water. If on clothes, remove clothes.
If breathed in, move person to fresh air.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for
additional health and safety information.**