

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixtures  
 Product name : FLUORESCENT ENAMEL PAINT  
 Product code : 1-35-21\*\*  
 Product group : Trade product

#### 1.2. Recommended use and restrictions on use

Coatings and paints

#### 1.3. Supplier

CONSOLIDATED COATINGS  
 7651 VANTAGE WAY  
 V4G 1A6  
 T 604-946-7626  
[Info@consolidatedcoatings.com](mailto:Info@consolidatedcoatings.com)

#### 1.4. Emergency telephone number

Emergency number : CANUTEC : 1-888-CAN-UTEC (226-8832) or 613-996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-CA)

Flammable liquids, H226  
 Category 3  
 Skin sensitisation, H317  
 Category 1  
 Germ cell mutagenicity, H340  
 Category 1B  
 Carcinogenicity, H350  
 Category 1B  
 Specific target organ H372  
 toxicity — Repeated  
 exposure, Category 1

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) :

- H226 - Flammable liquid and vapour.
- H317 - May cause an allergic skin reaction.
- H340 - May cause genetic defects.
- H350 - May cause cancer.
- H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-CA) :

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/lighting equipment.
- P242 - Use only non-sparking tools.
- P243 - Take action to prevent static discharges.
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-CA)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
chalk	AG stone	(CAS-No.) 1317-65-3	< 22.21776	Not classified
Stoddard solvent	Low boiling point naphtha - unspecified / Stoddard solvent	(CAS-No.) 8052-41-3	15.64115 - 16.57495	Not classified
solvent naphtha(petroleum), medium aliph.	Solvent naphtha (petroleum), medium aliph. / Straight run kerosine	(CAS-No.) 64742-88-7	~ 11.08	STOT RE 1, H372 Asp. Tox. 1, H304
talc	agalite	(CAS-No.) 14807-96-6	< 6.6432	Not classified
n-nonane	alkane C9	(CAS-No.) 111-84-2	0.4669 - 1.4007	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2,4-trimethylbenzene	1,2,4-TMB (=1,2,4-trimethylbenzene)	(CAS-No.) 95-63-6	0.4669 - 1.4007	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
Distillates (petroleum), hydrotreated light		(CAS-No.) 64742-47-8	~ 1.128	Asp. Tox. 1, H304
lecithins	1,2-diacyl-sn-glycero-3-phosphocholine	(CAS-No.) 8002-43-5	0.62	Not classified
Zirconium Carboxylate	METAL CARBOXYLATE	(CAS-No.) 22464-99-9	< 0.4335	Not classified
Mixed Calcium Carboxylates	Carcium Carboxylates		~ 0.423	Not classified
methanol	acetone alcohol	(CAS-No.) 67-56-1	0.3	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
Stoddard solvent, Low boiling point naphtha - unspecified	naphtha safety solvent	(CAS-No.) 8052-41-3	0.0459 - 0.201	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-butanone oxime	methyl ethyl ketone oxime	(CAS-No.) 96-29-7	> 0.1881	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
naphthalene	naphthalene	(CAS-No.) 91-20-3	0.04669 - 0.14127	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
ethylbenzene	EB (=ethylbenzene)	(CAS-No.) 100-41-4	0.04669 - 0.14127	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Chlorite-group minerals		(CAS-No.) 1318-59-8	> 0.1384	Not classified
dolomite	calcium magnesium carbonate	(CAS-No.) 16389-88-1	> 0.1384	Not classified
magnesium carbonate	carbonic acid magnesium salt	(CAS-No.) 546-93-0	> 0.1384	Not classified
cobalt(II) 2-ethylhexanoate	2-ethylhexanoic acid cobalt salt	(CAS-No.) 136-52-7	0.119 - 0.136	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
2-methyl-2,4-pentanediol	hexylene glycol	(CAS-No.) 107-41-5	0.0085 - 0.0425	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319
quartz, 1%≤conc respirable crystalline silica<10%	quartz (SiO <sub>2</sub> )	(CAS-No.) 14808-60-7	≤ 0.02224	Not classified
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	2-butoxyethoxyethanol	(CAS-No.) 112-34-5	< 0.018	Eye Irrit. 2, H319
butyl-2-propenoate/ethene,polymer	2-propenoic acid, butyl ester, polymer with ethene	(CAS-No.) 25750-84-9	< 0.00595	Not classified
2-butanol	1-methyl propanol	(CAS-No.) 78-92-2	< 0.00095	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 3, H336
methyl ethyl ketone	2-butanone	(CAS-No.) 78-93-3	< 0.00095	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
WATER		(CAS-No.) 7732-18-5	~ 0.000475	Not classified
vinyl acetate	1-acetoxyethene	(CAS-No.) 108-05-4	< 0.000085	Not classified

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
- First-aid measures general : IF exposed or concerned: Get medical advice/attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : May cause an allergic skin reaction.

#### 4.3. Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Unsuitable extinguishing media

No additional information available

#### 5.3. Specific hazards arising from the hazardous product

- Fire hazard : Flammable liquid and vapour.

#### 5.4. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.2. Methods and materials for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Other information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

n-nonane (111-84-2)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
1,2,4-trimethylbenzene (95-63-6)		
USA - ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ethylbenzene (100-41-4)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA - ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
Stoddard solvent (8052-41-3)		
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
2-methyl-2,4-pentanediol (107-41-5)		
USA - ACGIH	ACGIH TWA (ppm)	25 ppm
USA - ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA - ACGIH	ACGIH STEL (ppm)	50 ppm
USA - ACGIH	ACGIH Ceiling (ppm)	25 ppm (Hexylene glycol; USA; Momentary value; TLV - Adopted Value)
USA - ACGIH	Remark (ACGIH)	Eye & URT irr
vinyl acetate (108-05-4)		
USA - ACGIH	ACGIH TWA (ppm)	10 ppm
USA - ACGIH	ACGIH STEL (ppm)	15 ppm
methanol (67-56-1)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA - ACGIH	ACGIH STEL (ppm)	250 ppm (Methanol; USA; Short time value; TLV - Adopted Value)
USA - ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
quartz, 1%≤conc respirable crystalline silica<10% (14808-60-7)		
USA - ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (Respirable fraction)

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>talca (14807-96-6)</b>		
USA - ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Talc (containing no asbestos fibers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica; Talc (containing asbestos fibers); 0.1 fibers/cm <sup>3</sup> ; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination)
<b>dolomite (16389-88-1)</b>		
USA - ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (Respirable fraction)
<b>Stoddard solvent, Low boiling point naphtha - unspecified (8052-41-3)</b>		
USA - ACGIH	ACGIH TWA (ppm)	100 ppm (Stoddard solvent; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA - ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam; nausea; CNS impair
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>		
USA - ACGIH	ACGIH TWA (ppm)	10 ppm (Diethylene glycol monobutyl ether; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
<b>2-butanol (78-92-2)</b>		
USA - ACGIH	ACGIH TWA (ppm)	100 ppm (sec-Butanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA - ACGIH	Remark (ACGIH)	URT irr; CNS impair
<b>methyl ethyl ketone (78-93-3)</b>		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm (Methyl ethyl ketone (MEK); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA - ACGIH	ACGIH STEL (ppm)	300 ppm (Methyl ethyl ketone (MEK); USA; Short time value; TLV - Adopted Value)
USA - ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : No data available  
Colour : Mixture contains one or more component(s) which have the following colour(s):  
Colourless Pure substance: light yellow On exposure to air: yellow to brown Variable in colour, depending on the composition Colourless to light yellow No data available on colour  
Dark blue to violet White to light grey White to dark grey White Colourless to white

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Petroleum-like odour Almost odourless Aromatic odour Sweet odour Characteristic odour Mild odour Pleasant odour Alcohol odour Commercial/unpurified substance: Irritating/pungent odour Fruity odour Strong odour No data available on odour Ether-like odour Acetone odour Odourless
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 48 - 53 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative density	: No data available
Density	: 1.175 - 1.185 kg/l
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>n-nonane (111-84-2)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male/female, Read-across)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male/female, Read-across)
LC50 inhalation rat (mg/l)	17 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male, Literature)
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>ethylbenzene (100-41-4)</b>	
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
LD50 oral rat	3700 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value; > 2000 mg/kg bodyweight; Rat)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	> 8000 mg/kg (Rabbit)
<b>vinyl acetate (108-05-4)</b>	
LD50 oral rat	3470 mg/kg bodyweight (Rat, Male, Weight of evidence)
LD50 dermal rabbit	7440 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value)
LC50 inhalation rat (mg/l)	15.81 mg/l (4 h, Rat, Male/female, Weight of evidence)
LC50 inhalation rat (ppm)	4490 ppm (4 h, Rat, Male/female, Weight of evidence)
<b>methanol (67-56-1)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
<b>solvent naphtha(petroleum), medium aliph. (64742-88-7)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; Equivalent or similar to OECD 420; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
<b>chalk (1317-65-3)</b>	
LD50 oral rat	6450 mg/kg (Rat; Literature study)
<b>magnesium carbonate (546-93-0)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value)
<b>Stoddard solvent, Low boiling point naphtha - unspecified (8052-41-3)</b>	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 5.5 mg/l/4h (Rat)
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
LD50 oral rat	3129 mg/kg bodyweight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Weight of evidence)
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
<b>2-butanone oxime (96-29-7)</b>	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2326 mg/kg bodyweight; Rat; Experimental value; >900 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature)
LD50 dermal rabbit	> 1000 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	20 mg/l/4h (Rat; Literature study)
<b>2-butanol (78-92-2)</b>	
LD50 oral rat	2193 mg/kg (Rat)
LD50 dermal rat	> 2000 mg/kg (Rat)
LC50 inhalation rat (mg/l)	48.5 mg/l/4h (Rat)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.



# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Aspiration hazard : Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>n-nonane (111-84-2)</b>	
EC50 Daphnia 1	0.2 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value)
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
<b>ethylbenzene (100-41-4)</b>	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)
<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
LC50 fish 2	9450 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	5410 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
<b>vinyl acetate (108-05-4)</b>	
LC50 fish 1	14 - 44 mg/l (96 h, Pimephales promelas)
EC50 Daphnia 1	12.6 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
<b>methanol (67-56-1)</b>	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
<b>solvent naphtha(petroleum), medium aliph. (64742-88-7)</b>	
LC50 fish 1	2 - 5 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	1.4 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
<b>talc (14807-96-6)</b>	
LC50 fish 1	> 100 g/l (LC50; 24 h; Brachydanio rerio)
<b>magnesium carbonate (546-93-0)</b>	
LC50 fish 1	2120 - 2820 mg/l (96 h, Pimephales promelas, Static system, Fresh water, Read-across)
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
LC50 fish 1	1.512 mg/l (ASTM, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
LC50 fish 2	54.1 mg/l (ASTM, 96 h, Pimephales promelas, Flow-through system, Fresh water, Read-across)
EC50 other aquatic organisms 1	1703 mg/kg dwt (ASTM, 28 day(s), Tubifex tubifex, Semi-static system, Fresh water, Read-across)
ErC50 (algae)	144 µg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across)
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>	
LC50 fish 1	1300 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Lepomis macrochirus; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	> 100 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
<b>2-butanol (78-92-2)</b>	
LC50 fish 1	3670 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 2	2300 mg/l (EC50; 24 h)
<b>methyl ethyl ketone (78-93-3)</b>	
LC50 fish 2	2993 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)



# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>methyl ethyl ketone (78-93-3)</b>	
EC50 Daphnia 1	308 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>n-nonane (111-84-2)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

<b>1,2,4-trimethylbenzene (95-63-6)</b>	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O <sub>2</sub> /g substance

<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance
BOD (% of ThOD)	45.4 (20 days)

<b>lecithins (8002-43-5)</b>	
Persistence and degradability	Biodegradability in water: no data available.

<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
Persistence and degradability	Readily biodegradable in water. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.02 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.2 g O <sub>2</sub> /g substance
ThOD	2.3 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.01

<b>butyl-2-propenoate/ethene,polymer (25750-84-9)</b>	
Persistence and degradability	Biodegradability in soil: no data available. Biodegradability in water: no data available.

<b>vinyl acetate (108-05-4)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ThOD	1.7 g O <sub>2</sub> /g substance

<b>methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.8 (Literature study)

<b>solvent naphtha(petroleum), medium aliph. (64742-88-7)</b>	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.

<b>chalk (1317-65-3)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

<b>quartz, 1%≤conc respirable crystalline silica&lt;10% (14808-60-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>talc (14807-96-6)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

<b>dolomite (16389-88-1)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>dolomite (16389-88-1)</b>	
BOD (% of ThOD)	Not applicable
<b>magnesium carbonate (546-93-0)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.25 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.08 g O <sub>2</sub> /g substance
ThOD	2.173 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.11
<b>2-butanone oxime (96-29-7)</b>	
Persistence and degradability	Inherently biodegradable. No (test)data on mobility of the substance available.
<b>2-butanol (78-92-2)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	1.87 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.47 g O <sub>2</sub> /g substance
ThOD	2.59 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.72
<b>methylethyl ketone (78-93-3)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance
BOD (% of ThOD)	> 0.5 (5 days; Literature study)
<b>12.3. Bioaccumulative potential</b>	
<b>n-nonane (111-84-2)</b>	
BCF fish 1	8118 (Pimephales promelas, QSAR)
BCF other aquatic organisms 1	105 (BCFBAF v3.00, Calculated value)
Log Pow	5.65 (Literature)
Log Koc	2.9 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Log Koc	log Koc,3.04; Calculated value
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
<b>ethylbenzene (100-41-4)</b>	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Stoddard solvent (8052-41-3)</b>	
Log Pow	3.16 - 7.06
Log Koc	2.85 - 6.74 (log Koc)
<b>lecithins (8002-43-5)</b>	
Bioaccumulative potential	No bioaccumulation data available.

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
Log Pow	0.58 (QSAR)
Log Koc	Koc,Other; 1; Calculated value
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>butyl-2-propenoate/ethene,polymer (25750-84-9)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>vinyl acetate (108-05-4)</b>	
BCF fish 1	3.16 (Pisces, QSAR)
BCF other aquatic organisms 1	2.09 - 2.34 (QSAR)
Log Pow	0.73 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>methanol (67-56-1)</b>	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>solvent naphtha(petroleum), medium aliph. (64742-88-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>chalk (1317-65-3)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>quartz, 1%≤conc respirable crystalline silica&lt;10% (14808-60-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>dolomite (16389-88-1)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>magnesium carbonate (546-93-0)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>Stoddard solvent, Low boiling point naphtha - unspecified (8052-41-3)</b>	
Log Pow	-3.16 - 7.06
Bioaccumulative potential	Bioaccumable.
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
BCF fish 1	1.2 (131 day(s), Seriola quinqueradiata, Static system, Salt water, Read-across, Fresh weight)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>	
BCF fish 1	0.46 (BCF)
Log Pow	0.56 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>2-butanone oxime (96-29-7)</b>	
BCF fish 1	0.5-5.8,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; Cyprinus carpio; Fresh water; Experimental value
Log Pow	0.63 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>2-butanol (78-92-2)</b>	
Log Pow	0.61 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>methyl ethyl ketone (78-93-3)</b>	
Log Pow	0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Log Koc	Koc,34; Calculated value
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>12.4. Mobility in soil</b>	
<b>n-nonane (111-84-2)</b>	
Surface tension	22.38 mN/m (25 °C)
Log Pow	5.65 (Literature)
Log Koc	2.9 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>1,2,4-trimethylbenzene (95-63-6)</b>	
Surface tension	0.029 N/m
Log Pow	3.63 - 4.09 (Experimental value)
Log Koc	log Koc,3.04; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
<b>ethylbenzene (100-41-4)</b>	
Surface tension	0.029 N/m
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
<b>Stoddard solvent (8052-41-3)</b>	
Log Pow	3.16 - 7.06
Log Koc	2.85 - 6.74 (log Koc)
<b>2-methyl-2,4-pentanediol (107-41-5)</b>	
Surface tension	0.033 N/m
Log Pow	0.58 (QSAR)
Log Koc	Koc,Other; 1; Calculated value
<b>vinyl acetate (108-05-4)</b>	
Surface tension	0.024 N/m (20 °C)
Log Pow	0.73 (Experimental value)
Ecology - soil	Highly mobile in soil.
<b>methanol (67-56-1)</b>	
Surface tension	0.023 N/m (20 °C)
Log Pow	-0.77 (Experimental value; Other)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value
<b>quartz, 1%≤conc respirable crystalline silica&lt;10% (14808-60-7)</b>	
Ecology - soil	Low potential for mobility in soil.
<b>magnesium carbonate (546-93-0)</b>	
Ecology - soil	No (test)data on mobility of the substance available.
<b>Stoddard solvent, Low boiling point naphtha - unspecified (8052-41-3)</b>	
Surface tension	0.02 N/m (20 °C)
Log Pow	-3.16 - 7.06
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
Surface tension	0.064 N/m (20 °C, 1 g/l)
Ecology - soil	No (test)data on mobility of the substance available.
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>	
Surface tension	0.034 N/m (25 °C)
Log Pow	0.56 (Experimental value)
<b>2-butanone oxime (96-29-7)</b>	
Log Pow	0.63 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
<b>2-butanol (78-92-2)</b>	
Surface tension	0.023 N/m (20 °C)
Log Pow	0.61 (Experimental value)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
<b>methyl ethyl ketone (78-93-3)</b>	
Surface tension	0.024 N/m (20 °C)
Log Pow	0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Log Koc	Koc,34; Calculated value
Ecology - soil	Slightly harmful to plants.

### 12.5. Other adverse effects

GWPmix comment : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Additional information : Flammable vapours may accumulate in the container.

### SECTION 14: Transport information

#### 14.1. Basic shipping description

In accordance with TDG

#### Transportation of Dangerous Goods

UN-No. (TDG) : UN1263  
Packing group : III - Minor Danger  
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids  
Transport document description : UN1263 PAINT, 3, III  
Proper Shipping Name (Transportation of Dangerous Goods) : PAINT

Hazard labels (TDG) : 3 - Flammable liquids



TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass).

142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306

Explosive Limit and Limited Quantity Index : 5 L  
Excepted quantities (TDG) : E1  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 60 L

#### 14.2. Transport information/DOT

##### Department of Transport

Not regulated for transport

#### 14.3. Air and sea transport

##### IMDG

Not regulated for transport

##### IATA

Not regulated for transport

### SECTION 15: Regulatory information

#### 15.1. National regulations

##### n-nonane (111-84-2)

Listed on the Canadian DSL (Domestic Substances List)

##### 1,2,4-trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List)

##### ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

##### naphthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List)

##### Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>lecithins (8002-43-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>2-methyl-2,4-pentanediol (107-41-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>butyl-2-propenoate/ethene,polymer (25750-84-9)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>vinyl acetate (108-05-4)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>methanol (67-56-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>solvent naphtha(petroleum), medium aliph. (64742-88-7)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>chalk (1317-65-3)</b>
Listed on the Canadian NDSL (Non-Domestic Substances List)
<b>quartz, 1%≤conc respirable crystalline silica&lt;10% (14808-60-7)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>talc (14807-96-6)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Chlorite-group minerals (1318-59-8)</b>
Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)
<b>dolomite (16389-88-1)</b>
Listed on the Canadian NDSL (Non-Domestic Substances List)
<b>magnesium carbonate (546-93-0)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Stoddard solvent, Low boiling point naphtha - unspecified (8052-41-3)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Zirconium Carboxylate (22464-99-9)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>2-butanone oxime (96-29-7)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>2-butanol (78-92-2)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>methyl ethyl ketone (78-93-3)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>WATER (7732-18-5)</b>
Listed on the Canadian DSL (Domestic Substances List)

### 15.2. International regulations

<b>n-nonane (111-84-2)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>1,2,4-trimethylbenzene (95-63-6)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>ethylbenzene (100-41-4)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>naphthalene (91-20-3)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Stoddard solvent (8052-41-3)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory



# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>lecithins (8002-43-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>2-methyl-2,4-pentanediol (107-41-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>butyl-2-propenoate/ethene,polymer (25750-84-9)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>vinyl acetate (108-05-4)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>methanol (67-56-1)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>solvent naphtha(petroleum), medium aliph. (64742-88-7)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>chalk (1317-65-3)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>quartz, 1%≤conc respirable crystalline silica&lt;10% (14808-60-7)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>talc (14807-96-6)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Chlorite-group minerals (1318-59-8)</b>
Not listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>dolomite (16389-88-1)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>magnesium carbonate (546-93-0)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Stoddard solvent, Low boiling point naphtha - unspecified (8052-41-3)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Zirconium Carboxylate (22464-99-9)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>2-butanone oxime (96-29-7)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>2-butanol (78-92-2)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>methyl ethyl ketone (78-93-3)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>WATER (7732-18-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory

### SECTION 16: Other information

SDS Major/Minor	: None
Date of issue	: 04/08/2019
Revision date	: 04/08/2019
Supersedes	: 04/08/2019

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H301	Toxic if swallowed.
H302	Harmful if swallowed.



# FLUORESCENT ENAMEL PAINT

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

-----	H304	May be fatal if swallowed and enters airways.
-----	H311	Toxic in contact with skin.
-----	H312	Harmful in contact with skin.
-----	H315	Causes skin irritation.
-----	H317	May cause an allergic skin reaction.
-----	H318	Causes serious eye damage.
-----	H319	Causes serious eye irritation.
-----	H331	Toxic if inhaled.
-----	H332	Harmful if inhaled.
-----	H335	May cause respiratory irritation.
-----	H336	May cause drowsiness or dizziness.
-----	H340	May cause genetic defects.
-----	H350	May cause cancer.
-----	H351	Suspected of causing cancer.
-----	H370	Causes damage to organs.
-----	H372	Causes damage to organs through prolonged or repeated exposure.
-----	H373	May cause damage to organs through prolonged or repeated exposure.
-----	H400	Very toxic to aquatic life.
-----	H410	Very toxic to aquatic life with long lasting effects.
-----	H411	Toxic to aquatic life with long lasting effects.
-----	H412	Harmful to aquatic life with long lasting effects.

SDS Canada (GHS)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*