



# SILKS<sup>®</sup> INTERIOR LATEX EGGSHELL FINISH PS42

## Features

- Excellent hiding
- Low sheen finish
- Washable
- Easy application
- Soap and water clean up

## General Description

An interior latex paint that dries to a decorative eggshell finish. It features easy application; soap and water clean-up and a washable finish that is easy to keep clean.

## Recommended For

An interior eggshell finish for primed and previously painted walls and ceilings. Recommended for bedrooms, living rooms, dining rooms and hallways.

## Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)

## Product Information

<p><b>Colours: —Standard:</b></p> <p>Super White (May be tinted with up to 2.0 fl oz of universal colorants per 3.79L.)</p> <hr/> <p><b>—Tint Bases:</b></p> <p>Base 1, Base 2, Base 3, Base 4</p> <hr/> <p><b>—Special Colours:</b></p> <p>Contact your local Paint Shop Atlantic retailer</p> <hr/> <p><b>Certification:</b></p>	<table border="1"> <thead> <tr> <th>Technical Data<sup>∠</sup></th> <th>Pastel Base</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>Acrylic Blended Latex</td> </tr> <tr> <td>Pigment Type</td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td>31.5%</td> </tr> <tr> <td>Coverage per 3.79 L at Recommended Film Thickness</td> <td>37.2 – 41.8 sq. m. (400 – 450 sq. ft.)</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet 3.8 mils – Dry 1.2 mils</td> </tr> <tr> <td colspan="2">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 25 °C (77 °F) @ 50% RH</td> <td>– To Touch 2 Hours – To Recoat 4 Hours</td> </tr> <tr> <td colspan="2">Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times</td> </tr> <tr> <td>Dries By</td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity</td> <td>97 ± 3 KU</td> </tr> <tr> <td>Flash Point</td> <td>None</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Eggshell</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. 10 °C (50 °F) – Max 32.2 °C (90 °F)</td> </tr> <tr> <td>Thin With</td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Clean Water</td> </tr> <tr> <td>Weight Per 3.79 L</td> <td>4.9 kg (10.8 lbs.)</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 4.4 °C (40 °F) – Max 32.2 °C (90 °F)</td> </tr> <tr> <td colspan="2" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td colspan="2" style="text-align: center;">144 g/L</td> </tr> </tbody> </table>	Technical Data <sup>∠</sup>	Pastel Base	Vehicle Type	Acrylic Blended Latex	Pigment Type	Titanium Dioxide	Volume Solids	31.5%	Coverage per 3.79 L at Recommended Film Thickness	37.2 – 41.8 sq. m. (400 – 450 sq. ft.)	Recommended Film Thickness	– Wet 3.8 mils – Dry 1.2 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 2 Hours – To Recoat 4 Hours	Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times		Dries By	Evaporation, Coalescence	Viscosity	97 ± 3 KU	Flash Point	None	Gloss / Sheen	Eggshell	Surface Temperature at Application	– Min. 10 °C (50 °F) – Max 32.2 °C (90 °F)	Thin With	Clean Water	Clean Up Thinner	Clean Water	Weight Per 3.79 L	4.9 kg (10.8 lbs.)	Storage Temperature	– Min. 4.4 °C (40 °F) – Max 32.2 °C (90 °F)	Volatile Organic Compounds (VOC)		144 g/L	
Technical Data <sup>∠</sup>	Pastel Base																																								
Vehicle Type	Acrylic Blended Latex																																								
Pigment Type	Titanium Dioxide																																								
Volume Solids	31.5%																																								
Coverage per 3.79 L at Recommended Film Thickness	37.2 – 41.8 sq. m. (400 – 450 sq. ft.)																																								
Recommended Film Thickness	– Wet 3.8 mils – Dry 1.2 mils																																								
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.																																									
Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 2 Hours – To Recoat 4 Hours																																								
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times																																									
Dries By	Evaporation, Coalescence																																								
Viscosity	97 ± 3 KU																																								
Flash Point	None																																								
Gloss / Sheen	Eggshell																																								
Surface Temperature at Application	– Min. 10 °C (50 °F) – Max 32.2 °C (90 °F)																																								
Thin With	Clean Water																																								
Clean Up Thinner	Clean Water																																								
Weight Per 3.79 L	4.9 kg (10.8 lbs.)																																								
Storage Temperature	– Min. 4.4 °C (40 °F) – Max 32.2 °C (90 °F)																																								
Volatile Organic Compounds (VOC)																																									
144 g/L																																									
<p><b>Customer Information Centre:</b></p> <p>709-747-5432, <a href="mailto:info@thepaintshop.ca">info@thepaintshop.ca</a>, <a href="http://www.thepaintshop.ca">www.thepaintshop.ca</a></p>																																									

<sup>∠</sup>Reported values are for Pastel Base. Contact Paint Shop Atlantic for values of other bases or colours.

## Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

**Difficult Substrates:** For use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem, please call or visit your nearest Paint Shop Atlantic retailer for the right problem-solving primer.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php)

## Primer/Finish Systems

Silks® Interior Latex Primer is the preferred primer in most situations. For best hiding results use Silks® Primer tinted to the approximate finish coat colour. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

### Wood, and engineered wood products

**Primer:** Silks® Interior Latex Primer or All-Purpose Alkyd Primer  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

### Drywall

**Primer:** Silks® Interior Latex Primer  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

### Plaster

**Primer:** Silks® Interior Latex Primer  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

### Rough or Pitted Masonry

**Primer:** Latex Block Filler or Masonry Interior/Exterior Hi-Build Block Filler  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

### Smooth Poured or Pre-cast Concrete

**Primer:** Silks® Interior Latex Primer  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

### Ferrous Metal (Steel and Iron)

**Primer:** Acrylic Metal Primer, Alkyd Metal Primer or Rust Inhibitive Primer  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

**Non-Ferrous Metal (Galvanized & Aluminum)** All new metal surfaces must be thoroughly cleaned with Oil & Grease Emulsifier to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

**Primer:** Acrylic Metal Primer  
**Finish:** 1 or 2 coats Silks® Interior Latex Eggshell Finish

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

## Application

**Mixing of Paint:** Stir thoroughly before and during use. Apply one or two coats. **Paint Application:** For best results, use a professional custom-blended nylon/polyester brush, professional roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

**Spray, Airless:** Fluid Pressure — 1,500 or 2,500 PSI;  
Tip — .013 - .017 Orifice

## Thinning/Clean up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

**Clean up:** Clean brushes, rollers and other painting tools in warm soapy water after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

## Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional  
health and safety information.**