



Matchless MatGlo

21XX SERIE

Fluorescent Paint

Solid	Coverage	Film thickness recommended		
By weight: 65 ± 2 % By volume: 55 ± 2 %	75 m ² /gal (807 ft ² /gal) @ 1mil dry	1.5 to 2.0 mils dry (2 coats)		
Drying time	T° of resistance	Attributes	Shell life	Sheen
Touch free: 1 to 2 hrs Recoating time: 2 to 3 hrs Hard: 14 to 18 hrs	90° C, Continuous	Flexibility: Good Chemical resistance: Poor Weathering: Fair	Minimum 1 year	Low sheen
Thinner/Cleaner	Format	Viscosity		
545-151, 545-153 or 545-162	3,78l	91-93 K.U.		

Colors:

2101	Flame red	2107	Impact yellow
2103	Fire red	2108	Ember pink
2104	Flare orange	2109	Lightning yellow
2105	Signal green	2110	Blue

Description:

A general purpose daylight fluorescent and reflectance paint system, designed for application where high visibility is required. Its high visibility properties, makes it an exceptional coating for safety marking and life saving purposes. It is formulated with premium ingredients that provide durability for marine application.

Recommended uses:

Interior/exterior safety marking on properly primed surfaces.
Fire protection, life-saving equipment, navigational aids, etc.

Not recommended for:

Floors, concrete and alkaline surfaces.
Use in areas exposed to chemicals fumes. Immersion service.

Surface preparation:

- Previously painted surfaces should be dry, free of dirt, oil, loose paint, etc
- Wash off dirt with warm, soapy water and remove grease, wax and oil with a cloth dampened with mineral spirit or alkyd paint thinner.
- Remove rust by scraping, wire brushing or sanding.
- Surfaces to be painted should be at least 3°C above dew point, to prevent condensation during application. Do not apply on a damp surface or rainy day. Do not paint late in the day.

NOTES: IT IS ESSENTIAL THAT A COAT OF WHITE FLAT UNDERCOATER BE APPLIED TO ALL SURFACES BEFORE THE APPLICATION OF MATGLO FLUORESCENT PAINT. IT IS THE WHITE UNDERCOAT WHICH CONTRIBUTES TO THE LIGHT REFLECTANCE OF THIS TYPE OF PAINTS.

Method of application:

Brush & roller, maximum dilution: 5% by volume.
Spray, maximum dilution: 20% by volume.

KEEP AWAY FROM FLAMES OR EXCESSIVE HEAT
AND ANIMALS

KEEP OUT OF REACH OF CHILDREN

CONTACT YOUR MUNICIPALITY FOR DISPOSAL

Before using this product, read the material safety data sheet (MSDF) concerning the safety equipment to wear (section IX), for preventive measures (section VII), emergency and first aid treatments.

The information given above is provided by *Matchless Paint*. for information purposes only and in no way does it constitute a representation, promise or guarantee in regards to the usage, durability or quality of the product. The products identified above must be used in strict compliance with the specifications mentioned above and all other instructions, warnings or guidelines issued by *Matchless Paint*

FT002-1XXX

17/04/01