HOW TO PAINT VINYL SIDING

INSTRUCTIONS

SH				

☐ Benjamin Moore Element Guar	d Exterior Paint	Fresh Start High Hiding Exterior Primer			
Benjamin Moore Clean	Angular Brush	☐ Handy Paint Pail			
5-Gallon Pail to Mix Cleaner					

PREP

- 1. Clean your vinyl siding so the surface is free of dirt or mildew, either by hand or with a power washer. **Benjamin Moore Clean** multi-purpose cleaner is recommended for best results.
- 2. Be careful of water seeping under the siding, around windows, doors, vents, soffits, and other openings. Hold the nozzle facing down to avoid forcing water under the siding panels.
- 3. Let dry.

PRIME

1. In most cases priming is not necessary. Only areas of pitted or porous vinyl siding must be primed. When needed, use **Fresh Start High Hiding Exterior Primer**.

PAINT

- 1. Paint on a dry but cloudy day with the temperature above 1.7°C. Do NOT paint in direct sunlight.
- 2. Using **Element Guard Exterior Paint**, choose one of our 75+ vinyl-safe colours that are guaranteed not to warp vinyl siding.
- 3. Using a paint brush, apply paint making sure to remove any drips.
- 4. Paint multiple thin coats rather than one thick coat for better results.
- 5. Make sure to paint underneath the seams in the siding. This will prevent the older colour from showing when the vinyl siding expands and contracts as the temperature changes.
- 6. Allow first coat to dry completely before applying the second coat.

MORE QUESTIONS? Contact your local **Benjamin Moore Paint Shop** and our expert staff will be happy to help. Visit our website at **paintshop.ca** to find a location near you.

